

### GENERAL DESCRIPTION

AXEL SOLVENT 914 is a hydrocarbon solvent that widely used in paint and chemical industrial as cleaning agent or thinner.

### RECOMMENDED USES

Use as cleaning agent for tools, equipment and contaminants removal.

### COLOURS

Colourless

### PACKING

1 litre, 5 litres and 20 litres per pail

### METHOD OF APPLICATION

- \* Apply AXEL SOLVENT 914 over contaminated surface and removed with cloth. Rinse surface thoroughly with clean water and allow to dry.
- \* Used in a well-ventilated area.
- \* Wear protective gloves/protective clothing/eye protection/face protection to avoid irritation.

### TECHNICAL SPECIFICATIONS

No. of components	One
Appearance	Clear liquid
Specific gravity (25°C)	0.85-0.87 kg/l
Flash point	27°C
Odor	Aromatic hydrocarbon

### STORAGE

Store tightly sealed containers away from direct sunlight or sources of heat.

### SHELF LIFE

12 months from the date of production if stored properly in original, unopened and undamaged sealed packaging in dry conditions.

The above data is provided in good faith and to the best of our knowledge. However, since application and services conditions are beyond our control, we do not accept liability relating to coverage, performance and injury arising from the use of our products based on the data. Further with the constant advancement of technology we reserve the right to modify data without prior notice and we advise that you check with our Axelchem Technical Department at Tel: 603-6276 2118 the validity of these data especially if more than six months have lapsed since issue.